


**EFFER**
**iX.550<sup>HP</sup>**
**TECHNICAL DATA SHEET**

**51tm range loader crane**

- SPACEevo control system.
- Variable pump, for increased flow performances and reduced fuel consumption.
- Nano based technology coating.
- CE marked.

**Standard and optional features:**

- XS Drive remote control (s).
- CombiDrive 4 remote control (o).
- E-6, E-7 and E-8 versions with optional JIB 150X-6.

Description	Unit	E-4	E-5	E-6	E-6 JIB150 X-6	E-7	E-7 JIB 150 X-6	E-8	E-8 JIB150 X-6	E-9
Max. net lifting moment	kgm/ kNm	477/48.6	470/47.9	462/47.1	462/47.1	456/46.5	456/46.5	449/45.8	449/45.8	444/45.3
Slewing arc	(°)	Continuous	Continuous	Continuous	Continuous	Continuous	Continuous	Continuous	Continuous	Continuous
Slewing caapcity-max slope	(°)	5	5	5	5	5	5	5	5	5
Max oil delivery	l/min	100-140	100-140	100-140	100-140	100-140	100-140	100-140	100-140	100-140
Max. outreach, hydraulic extensions	m	11.2	13.5	15.4	-	17.6	-	19.6	-	21.8
Max. Outreach, with manual extension	m	-	-	-	-	-	-	-	-	24.0
Outreach, with JIB	m	-	-	-	27.6	-	29.6	-	31.7	-
Outreach, with JIB, with manual extension	m	-	-	-	29.1	-	31.2	-	33.2	-
Weight standard crane (±2%), incl supporting legs	kg	5296	5598	5782	7106	5968	7326	6198	7524	6379

(s) = Standard, (o) = Optional